




# ROMET

# Rotary Gas Meters



#### Note: AMI/AMR adaptors available upon request.

METER SIZE	ANSI 125 FF FLANGE	А	В	С	D1	D2	D3	D4	D5	D6	E1	E2	WEIGHT (lbs)
RM3000	2"	6.75"	Ø 6.0"	5.58"	14.93"	16.36"	17.19"	18.13"	17.48"	17.53"	4.00"	4.00"	27-36

# RM3000 - IMPERIAL

## IMPERIAL RM3000 2" FLANGE CONNECTION

## TECHNICAL SPECIFICATION


Connection (Flanged)	ANSI 125 FF	2"
MAOP	(psig)	175
Flow Capacity	(cfh)	3000
Rangeability* (up to 1:160 @ atmospheric condition)		1:160
Start Rate	(cfh)	4.0
Stop Rate	(cfh)	3.3
Differential @ 100% Flow	(I.W.C.)	0.86
Instrument Drive Rate	(cf/rev)	10/100
LF Pulser (Optional)	(cf/pulse)	10/100

<sup>\*</sup>Note: It should be noted, that moving parts in the meters with greater rangeability ratio are made to high class accuracy and tight tolerances.

Improper installation, stresses on piping system due to temperature changes, settling and gas conditions can create a risk of meter rejection.

### CORRECTED FLOW CAPACITY AND TYPICAL ACCURACY GUIDE

RM3000 METER (SCFH)				
Gauge Pressure P.S.I.G. 0.25	RM3000 Qmax = 3000ft <sup>3</sup> /hr			
2	3136			
5	3951			
10	4969			
15	5988			
20	7006			
25	8024			
50	13116			
75	18208			
100	23299			
125	28391			
150	33483			
175	38574			





## ROMET

#### GAS METERS AND ELECTRONIC INSTRUMENTS

Phone 905-624-1591 USA 1-800-387-3201 www.rometlimited.com • email: romet@rometlimited.com

The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked. However, Romet Limited will not assume responsibility for any possible omissions or errors.